

# WEITZNER

## Hanging Instructions

### Fit to Print W5011

#### APPLICATION

For Type II wallcoverings, use Roman® ECO-778 or equivalent clay-based adhesive.

##### Wet hang:

For this hanging method, the adhesive can be diluted with water according to the manufacturer's instructions. Apply a liberal, even coat of adhesive over the entire back of the wallcovering with either a commercial pasting machine or a roller. Allow the material to book for 15 minutes before installation.

##### Dry Hang:

For this hanging method, do not dilute the adhesive. Roll a liberal, even coat of the full strength adhesive on the wall.

For difficult installations, such as columns or outside corners, apply the adhesive to both the wall and the back of the wallcovering and allow each surface to "tack up" before installation.

Do not use steel-blade knives for smoothing the wallcovering or seams, as the steel will damage the vinyl surface.

To prevent discolored seams and dull areas on the face of this product, it is important to carefully wash the excess adhesive from seams after installing each strip. Use a sponge dampened with clean, warm water, changed frequently, and dry with a clean, soft towel.

To assure a uniform installation, examine all wallcoverings for color and repeat designs before beginning. Determine if the color and texture requires the pattern to be lined up, matched and/or alternately reversed.

Vinyl wallcovering can act as a vapor barrier and consequently should not be installed on walls that are susceptible to excessive condensation or moisture infiltration.

This wallcovering can be made permeable by a micro-venting process (minimum 8+ perms). However, permeable wallcovering cannot compensate for water intrusion caused by poor building envelope design, faulty construction, building system failure or improper maintenance practices.

Existing mold or mildew must be removed from walls, followed by treatment to inhibit further growth. Refer to the EPA website for guidelines at [www.epa.gov](http://www.epa.gov).

The wallcovering must be allowed to warm up to a minimum of 70° F (21° C) before installation, if stored or transported at cold temperatures.

The weight of this product is above average (approximately 2lbs/yd).

This wallcovering should not be reverse hung when installed.

\$3.00/yard additional fee for orders below 30 yards.

#### RECOMMENDATIONS

Weitzner recommends hiring a professional wallcovering installer. For a list of professional installers near you please visit [www.wallcoveringinstallers.org](http://www.wallcoveringinstallers.org).

Always make sure the surface you are hanging on has been properly prepared. Walls should be clean, smooth, dry and structurally sound. Repair any holes or flaws in the walls prior to installing wallcovering.

Make sure your tools, hands and workspace are always clean. Please handle with care, never crease the wallcovering and avoid touching the face.

We recommend priming walls before installing the wallcovering using Zinsser® Shieldz® or equivalent. Do not hang wallcovering directly on an oil-based primer.

# WEITZNER

## Hanging Instructions

### Fit to Print W5011

Always apply an even coat of paste to either the wall or the back of the wallcovering. If you choose to apply the paste directly to the back of the wallcovering, handle with care during installation.

Always use a new blade for each cut and take care not to overwork or stretch seams.

After installing a maximum of three sheets, inspect application. If satisfactory, continue. If not, discontinue and contact your local sales representative.

Note: The manufacturer assumes no responsibility for installation of material beyond three sheets and will not be held responsible for labor under any circumstances.

For product specifications and installation videos, please visit [www.weitznerlimited.com](http://www.weitznerlimited.com).

## CARE INSTRUCTIONS

Please wipe with clean, white, damp cloth.